



## Premium Product

- >Multi-touch
- >Precision Engineering
- >Eye-Catching

### 32 Inch Open Frame Touch Monitor

OTL326 is a LED industrial Touchmonitor, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the OTL326 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

#### Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation

#### Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

## SPECIFICATIONS

Name	32 Inch Open Frame Touch Monitor
Model	OTL326
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	698.4×392.86mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	6.5ms
Display Colors	16.7million
Luminance (Typ.)	400nits; with P-Cap 340nits
Contrast Ratio (Typ.)	4000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened
	Optional: Anti-Glare
Active Area(W x H)	698.4×392.86±0.3mm
Thickness(Total)	3.3±0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 200×200 mm; Side Mounting
Outline Dimensions (W×H×D)	See The Drawing
Power Supply	Input Voltage Range: 100-240V AC, 50-60 Hz
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 60W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	910mm (L) × 220mm (W) × 630mm (H)
Weight	Net: 13.6kg Gross: 20.5kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE , FCC
Warranty	3 years

### Ordering Information

Model	Part Number	Description
OTL326-RC4000-UH4F00-1.0		32", 16:9, 400nits, P-Cap, USB, VGA & HDMI, Gray

*Contact sales for other options*

### Optional Accessories

Model	Part Number	Description
Power Cord	130300338R	UK
	130300339R	EU
	130300340R	US
HDMI Cord	130300881R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.