



## 55 Inch Closed Frame Touch Monitor

OTL555, a LED industrial Touchmonitor, is suited for applications in meeting rooms, classrooms, and digital signage. With low power consumption, high brightness, 4K resolution, ultra-thin body design, and high-resolution display, the OTL555 industrial-grade high performance and professional design deliver an excellent multi-touch interactive experience.

## Features & Benefits

- P-Cap technology
- 4K resolution
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation





## Applications

- Retail
- Kiosk
- Medical
- Finance
- Self-service
- Transport

Gaming



## **SPECIFICATIONS**

Name	55 Inch Closed Frame Touch Monitor		
Model	OTL555		
LCD Panel Parameters			
Display Technology	Active Matrix TFT-LCD With LED Backlight		
Aspect Ratio	16:9		
Active Area (W x H)	1209.6×680.4mm		
Native Resolution	3840×2160@60Hz		
Response Time (Typ.)	8ms		
Display Colors	1.07G		
Luminance (Typ.)	800nits; with P-Cap 665nits		
Contrast Ratio (Typ.)	1200:1		
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10.89° /89°  Vartical (un/lawn) CR>10.80° /80°		
Touch Screen Parameters	Vertical (up/down) CR≥10 89° /89°		
Touch Technology	Projected Capacitive (P-Cap)		
	Strengthened Strengthened		
Surface Treatment	Optional: Anti-Glare		
Active Area(W x H)	1211.6×682.4±0.5mm		
Thickness(Total)	$4.8\pm0.3$ mm		
Light Transmission	≥83%		
Response Time	10ms		
Touch Screen Interface	USB		
Touch Point	10		
Overall Parameters			
Case/Bezel Color	Silver middle frame with black back cover		
Mounting Options	VESA: 400 × 400 mm		
Outline Dimensions ( $W \times H \times D$ )	1259.4mm × 736.4mm× 72.8mm		
Power Supply	Input Voltage Range: 100-240V AC, 50-60 Hz		
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu		
Power Consumption	MAX: 186W		
Speaker	NA		
Webcam	NA		



Operating Altitude	≦3000m
Temperature Range	Operating: $0^{\circ}$ C to $40^{\circ}$ C, storage: $-20^{\circ}$ C to $60^{\circ}$ C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	DVI, HDMI, DP, USB (Type B, For touch)
Accessories	Cable: USB × 1, 1.5m Length
Carton Box Dimensions	$1390\text{mm (L)} \times 190\text{mm (W)} \times 850\text{mm (H)}$
Weight	Net: TBC Gross: TBC
MTBF	50,000 hours demonstrated
Agency Approvals	CE FCC
87FF	

Ordering Information		
Model	Part Number	Description
OTL555-RC5000-UD8U00-1.0	TBC	55", 16:9, 4K, 800nits, P-Cap, USB, DVI& HDMI & DP

# Contact sales for other options

Optional Accessories			
Model	Part Number	Description	
	130300338R	UK	
Power Cord	130300339R	EU	1500mm
	130300340R	US	
HDMI Cord	130300881R	1500mm	
DP Cord	130300932R	1500mm	
DVI Cord	130300720R	1500mm	

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.