

# TEF-22

## P-CAP



# TEF-22

Optional remote key with  
1.5 meter cable



OSD Controls



# Features

Cable cover



Vesa 100x100 mount or bracket mount



Widescreen



# Specification



TEF-22	
Size	21.5" TFT LCD
Maximum Resolution	1920 x 1080
Contrast Ratio	1000:1
Brightness (Backlight Type)	250 nits (No Touch), 225 nits (Projected Capacitive)
View Angle	H:178°, V:178°
Touch LCD Display	
Touch Type	Projected Capacitive
Touch points	10
Touch Screen Interface	USB-HID (Type B)
I/O Port	
Serial Port	1 x RJ11 (for Remote Key)
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA (DB15), 1 x DVI
Power Input	1 x 2.1 mm 12V DC Jack
Physical Properties	
Power Supply	50W (12V, 4.16A) External Power Adaptor
Speaker	NA
Housing Color	Black, Silver (No Paint on Back)
Construction	Glass, SECC Metal
Compliance	IP54 Compliant Front Side, IPX1
Dimensions (W x H x D) mm	517.4 x 313.3 x 46.0 mm
Net Weight (kg)	4.4 kg
Gross weight (kg)	6.8 kg
Carton (W x H x D) mm	405.0 x 610.0 x 160.0 mm
VESA	100 x 100 mm
Safety	
Certifications	BSMI, CCC, CE, FCC, RoHS, UL, cUL
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH, Non-Condensing
Option	
Remote Key	1.5 meter RJ11 Cable, Controls: Power, Select, Up, Down, Menu