

TEM-22

P-CAP



TEM-22

OSD Controls



Features

Vesa 100x100 mount or bracket mount



Widescreen



Specification

TEM-22	
Size	21.5" TFT LCD
Maximum Resolution	1920 x 1080
Contrast Ratio	1000:1
Brightness (Backlight Type)	250 nits (No Touch), 225 nits (Projected Capacitive)
View Angle	H:178°, V:178°
Touch LCD Display	
Touch Screen	Projected Capacitive
Touch Points	10 Points
Touch Screen Interface	USB-HID (Type B)
IO ports	
Serial Port	1 x RJ11 (for Remote Key)
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA (DB15), 1 x HDMI, 1 x DP
Audio Port	NA
Power Input	1 x 2.1 mm 12V DC Jack
Physical Properties	
Power Supply	50 W (12V / 4.16A) External Power Adaptor
Speaker	NA
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	IP65 Compliant Front Side, IPX1
Dimensions (W x H x D) mm	517.4 x 351.7 x 219.0 mm (With Stand), 517.4 x 313.3 x 46.0 mm (Without Stand)
Net Weight (kg)	7.8 kg
Gross Weight (kg)	10.8 kg
Carton (W x H x D) mm	450.0 x 615.0 x 330.0 mm
VESA	100 x 100 mm
Safety	
Certifications	BSMI, CCC, CE, FCC B Class, RoHS, UL, cUL
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing