

TSF-15

P-CAP



TSF-15

OSD Controls



Vesa 100x100 mount or side mount



Specification

TSF-15	
Size	15" TFT LCD
Maximum Resolution	1024 x 768
Contrast Ratio	700:1
Brightness (Backlight Type)	250 nits (No Touch), 225 nits (Projected Capacitive)
View Angle	H:140°, V:160°
Touch LCD Display	
Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Type B)
IO ports	
Serial Port	1 x RJ11 (For remote key)
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA (DB15), 1 x DVI
Audio Port	NA
Power Input	1 x 2.1 mm 12V DC Jack
Physical Properties	
Power Supply	50W (12V / 4.16A) External Power Adaptor
Speaker	NA
Housing Color	Black, Silver (No Paint on Back)
Construction	Glass, SECC Metal
Compliance	IP65 Compliant Front Side, IPX1
Dimensions (W x H x D) mm	337.4 x 265.4 x 44.3 mm
Net Weight (kg)	2.7 kg
Gross Weight (kg)	4.0 kg
Carton (W x H x D) mm	355.0 x 435.0 x 165.0 mm
VESA	100 x 100 mm
Safety	
Certifications	CCC, CE, FCC B Class, RoHS, UL, cUL
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing