

WTM270TR



ADVANTAGES

- ▶ Easy to Deploy
- ▶ High Definition
- ▶ Multi Platform Support
- ▶ PCT Multi-touch Film
- ▶ Flexible Installation
- ▶ Durable and Professional Embedded Design



TECHNICAL SPECIFICATIONS

WTM-Series Embedded Touch All-in-one Focus on Industry Touch and Display Solutions

Ver:May2018_V1

| LCD Panel | |
|-----------------------|--|
| Backlight | LED |
| Brightness | 300 cd/m ² |
| Contrast Ratio | 3000:1 |
| Viewing Angle | H:178° / V:178° |
| Response Time | 12 ms (GTG) |
| Supported Colors | 16.7M Colors |
| Display Resolution | 1920x 1080 (16:9) |
| Display Frame Rate | 60Hz |
| Input Resolution | 1920 x 1080 @ 60Hz(Analog) 1920 x 1080 @ 60Hz(Digital) |
| Touch | |
| Touch points | 10 |
| Touch technology | Projected Capacitive (PCT) |
| Mechanical | |
| Dimensions | 662.3 x 400.9 x 42.5 mm |
| Package Dimension | TBD |
| Weight(approximately) | 8 kg / 10 kg |
| Wall Mount Type | VESA,MIS-D,100,C |
| Connector | 1x VGA /1x DVI /1x HDMI |
| Operation | 0 °C ~ 50 °C, 90% RH |
| Storage | -20 °C ~ 60 °C, 90% RH |
| Electrical | |
| Power Supply | DC in: DC 12V 5A Max |
| Normal Operation | ≤ 32W (typ.) |
| Power Off | ≤ 2 W (typ.) |
| Internal Speaker | no |
| Android(Options) | |
| CPU | RK3188 Cortex-A9 RK3288 Cortex-A17 |
| Memory | 2GB DDR3 |
| Memory | 8GB EMMC NAND |
| ROM | 2xUSB /1xLAN /1xHDMI / 1xTF |
| Connector | Signage Software |
| Windows(Options) | |
| CPU | Celeron 3855U 1.6GHz i3 4005U 1.7GHz i5 4250U 1.3GHz |
| GPU | Intel® HD Graphics |
| Memory | 4GB DDR3 |
| Disk | 120G SSD/500G HDD |
| LAN | LAN 10/100/1000 Mbps |
| WIFI | 802.11 b/g/n |
| Connector | 4xUSB /1xLAN /1xHDMI |

