

WTM320TL



ADVANTAGES

- ▶ Easy to Deploy
- ▶ High Definition
- ▶ Flat Surface Design
- ▶ PCT Multi-touch Film
- ▶ Flexible Installation
- ▶ OPS Pluggable Computer



TECHNICAL SPECIFICATIONS

WTM-Series Touch All-in-one With PCT Focus on Industry Touch and Display Solutions

Ver:Jun2018_V1

> LCD Panel

Backlight	LED
Brightness	300 cd/m ²
Contrast Ratio	1200:1
Viewing Angle	H:178° / V:178°
Response Time	8 ms (GTG)
Supported Colors	16.7M Colors
Display Resolution	1920x 1080 (16:9)
Display Frame Rate	60Hz
Input Resolution	1920 x 1080 @ 60Hz(Analog) 1920 x 1080 @ 60Hz(Digital)

> Touch

Touch points	10/no
Touch technology	Projected Capacitive (PCT)

> Mechanical

Dimensions	760.8 x 455.4 x 55 mm
Package Dimension	904 x 200 x 585 mm
Weight(approximately)	17 kg / 21 kg
Wall Mount Type	VESA,MIS-F,300x200,Y,6,90
Connector	2x HDMI / 1x VGA
Operation	0 °C ~ 50 °C, 90% RH
Storage	-20 °C ~ 60 °C, 90% RH

> Electrical

Power Supply	AC in: AC 100V ~ 240V (50/60 Hz)
Normal Operation	≤ 36W (typ.)
Power Off	≤ 2 W (typ.)
Internal Speaker	2×8Ω/5W

> OPS Module (Options1)

CPU	A3->i3 4005U 1.7GHz A5->i5 4200U 1.6GHz
GPU	Intel® HD Graphics
Memory	4GB DDR3
Disk	500G HDD/120G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	6xUSB /1xLAN /1xHDMI /1xVGA

> OPS Module (Options2)

CPU	A7->i7 3520M 2GHz
GPU	Intel® HD Graphics
Memory	8GB DDR3
Disk	240G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	2xUSB /1xLAN /1xHDMI

