

WTM550UL



ADVANTAGES

- ▶ Easy to Deploy
- ▶ Ultra High Definition
- ▶ Flat Surface Design
- ▶ PCT Multi-touch Film
- ▶ Flexible Installation
- ▶ OPS Pluggable Computer



TECHNICAL SPECIFICATIONS

WTM-Series Touch All-in-one With PCT Focus on Industry Touch and Display Solutions

> LCD Panel

Backlight	LED
Brightness	450 cd/m ²
Contrast Ratio	1200:1
Viewing Angle	H:178° / V:178°
Response Time	8 ms (GTG)
Supported Colors	1.06B Colors
Display Resolution	3840 x 2160 (16:9)
Display Frame Rate	60Hz
Input Resolution	1920 x 1080 @ 60Hz (VGA) 3840 x 2160 @ 30Hz (HDMI1.4)

> Touch

Touch points	10/no
Touch technology	Projected Capacitive (PCT)

> Mechanical

Dimensions	1284.4 x 755.2 x 80.7 mm
Package Dimension	1488 x 963 x 210 mm
Weight(approximately)	50 kg / 60 kg
Wall Mount Type	VESA,MIS-F,600(400)x400,Y,8,90
Connector	1xHDMI/1xVGA/1xDVI
Operation	0 °C ~ 50 °C, 90% RH
Storage	-20 °C ~ 60 °C, 90% RH

> Electrical

Power Supply	AC in: AC 100V ~ 240V (50/60 Hz)
Normal Operation	≤ 97W (typ.)
Power Off	≤ 2 W (typ.)
Internal Speaker	2×8Ω/5W

> OPS Module (Options1)

CPU	A3->i3 4005U 1.7GHz A5->i5 4200U 1.6GHz
GPU	Intel® HD Graphics
Memory	4GB DDR3
Disk	500G HDD/120G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	6xUSB /1xLAN /1xHDMI /1xVGA

> OPS Module (Options2)(no support 4K)

CPU	A7->i7 3520M 2GHz
GPU	Intel® HD Graphics
Memory	8GB DDR3
Disk	240G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	2xUSB /1xLAN /1xHDMI

